



| | | | | | | | | |
|---------------------------------|--------------|-------------|---------------------------|--|------|---|---|----|
| BLOWDOWN SEP. CONNECTIONS | | PIPING DATA | | REVISIONS | | THIS DRAWING IS THE PROPERTY OF SUPERIOR BOILER AND SHALL NOT BE REPRODUCED IN PART OR IN WHOLE, AND NONE OF ITS INFORMATION SHALL BE REVEALED WITHOUT PERMISSION OR TO THE DETRIMENT OF THE OWNER. IT MUST BE RETURNED UPON REQUEST. | | |
| A. (1) VENT | 3 FLANGE | IN. | SHUTOFF VALVE | LTR. | DATE | | | BY |
| B. (1) DRAIN | 2 1/2 FLANGE | IN. | APOLLO 70-105-01 | | | | | |
| C. (1) INLET | 1 | IN. | CHECK VALVE | | | | | |
| D. (2) PORT | 2 | IN. | POWELL SW081A58GB | | | | | |
| E. () | | IN. | STRAINER | | | | JOB: _____ | |
| F. () | | IN. | KECKLEY STYLE B | | | | | |
| AFTERCOOLER CONNECTIONS | | | REG VALVE | | | | | |
| | | | WMCD W91-05-08SB15-C14U | | | | | |
| | | | SIZE 1" | | | | | |
| G. (1) DISCHARGE | 2 1/2 FLANGE | IN. | TEMP. GAUGE | TANK WEIGHT: 155 LBS. W/ AFTERCOOLER: 171 LBS. CODE: SECTION VIII, DIV 1 | | | Superior Boiler reserves the right to furnish trim shown or an equal substitute as determined by Superior Boiler. | |
| H. (1) WATER CONN. | 1 | IN. | | | | | | |
| J. (1) TEMP.BULB | 3/4 | IN. | | | | | | |
| K. (1) TEMP. GAUGE | 1/2 | IN. | | | | | | |
| L. () | | IN. | | | | | | |
| M. () | | IN. | MAKE WKA TL30 30060D206G4 | | | | DRAWING NAME BLOWDOWN SEPARATOR SYSTEM | |
| SIZE 3" DIA. 0-250. 1/2"NPT IN. | | | | | | | | |
| | | | | | | | | |
| | | | | MODEL NO: SBDS-1032-132.5-AC | | | | |
| | | | | PRESSURE: 150 PSI | | | | |
| | | | | SCALE 1/16 | | | | |
| | | | | DRAWING No | | | | |
| | | | | X | | | | |