



BLOWDOWN SEP. CONNECTIONS		PIPING DATA		REVISIONS		THIS DRAWING IS THE PROPERTY OF SUPERIOR BOILER AND SHALL NOT BE REPRODUCED IN PART OR IN WHOLE AND NONE OF ITS INFORMATION SHALL BE REVEALED WITHOUT PERMISSION OR TO THE DETRIMENT OF THE OWNER. IT MUST BE RETURNED UPON REQUEST.					
A. (1) VENT	4 FLANGE	IN.	SHUTOFF VALVE APOLLO 70-105-01	LTR.	DATE	BY	SOLD TO:				
B. (1) DRAIN	4 FLANGE	IN.	CHECK VALVE POWELL SW081A58GB				JOB:				
C. (1) INLET	1 1/4	IN.	STRAINER KECKLEY STYLE B				DRAWN BY: X DATE X CHECKED BY: DATE				
D. (2) PORT	2	IN.	REG VALVE WM&D W91-05-08SB15-C14U				BLOWDOWN SEPARATOR SYSTEM				
E. ()		IN.	SIZE 1"	TANK WEIGHT: 231 LBS. W/ AFTERCOOLER: 312 LBS. CODE: SECTION VIII DIV 1.			MODEL NO: SBDS-1630-1.2544-AC				
F. ()		IN.	TEMP. GAUGE				PRESSURE: 150 PSI				
AFTERCOOLER CONNECTIONS			MAKE WKA TL30 30060D206G4				SCALE 1/16				
			SIZE 3" DIA, 0-250, 1/2" NPT IN.				DRAWING No X				
G. (1) DISCHARGE	4 FLANGE	IN.		Superior Boiler reserves the right to furnish trim shown or an equal substitute as determined by Superior Boiler.			BLOWDOWN SEPARATOR SYSTEM				
H. (1) WATER CONN.	1 1/4	IN.					MODEL NO: SBDS-1630-1.2544-AC				
J. (1) TEMP. BULB	1	IN.					PRESSURE: 150 PSI				
K. (1) TEMP. GAUGE	1/2	IN.					SCALE 1/16				
L. ()		IN.					DRAWING No X				
M. ()		IN.									