





BLOWDOWN SEP. CONNECTIONS	
A. (1) VENT	5 FLANGE IN.
B. (1) DRAIN	4 FLANGE IN.
C. (1) INLET	1 1/4 IN.
D. (2) PORT	2 IN.
E. ( )	IN.
F. ( )	IN.

AFTERCOOLER CONNECTIONS	
G. (1) DISCHARGE	4 FLANGE IN.
H. (1) WATER CONN.	1 1/4 IN.
J. (1) TEMP.BULB	1 IN.
K. (1) TEMP. GAUGE	1/2 IN.
L. ( )	IN.
M. ( )	IN.

PIPING DATA
SHUTOFF VALVE APOLLO 70-105-01
CHECK VALVE POWELL SW08TA58GB
STRAINER KECKLEY STYLE B
REG VALVE WMcD W91-05-08SB15-C14U
SIZE 1"

TEMP. GAUGE
MAKE WIKA TI.30 30060D206G4
SIZE 3" DIAL, 0-250', 1/2"NPT IN.

REVISIONS

LTR.	DATE	CHANGE	BY

TANK WEIGHT: 272 LBS.

W/ AFTERCOOLER: 353 LBS.

CODE: SECTION VIII DIV 1.

Superior Boiler reserves the right to furnish trim shown or an equal substitute as determined by Superior Boiler.

THIS DRAWING IS THE PROPERTY OF SUPERIOR BOILER AND SHALL NOT BE REPRODUCED IN PART OR IN WHOLE, AND NONE OF ITS INFORMATION SHALL BE REVEALED WITHOUT PERMISSION OR TO THE DETRIMENT OF THE OWNER, IT MUST BE RETURNED UPON REQUEST.

SOLD TO: X

JOB: X

DRAWN BY:	DATE	CHECKED BY:	DATE
X			

DRAWING NAME

BLOWDOWN SEPARATOR SYSTEM

MODEL NO: SBDS-1638-1.2554-AC

PRESSURE: 300 PSI

SUPERIOR BOILER

SCALE 1/16

DRAWING No X