



BOILER CONNECTIONS

RATINGS & CAPACITIES

LTR DATE

REVISION

BY REPRESENTATIVE:

A.(1) WATER OUTLET 10" 150# FLG	HORSEPOWER 500
B.(1) WATER RETURN 10" 150# FLG	DESIGN PRESSURE 30 PSIG
C.(4) LWCO 1" NPT	DESIGN TEMPERATURE 250°F
D.(2) SAFETY VALVE 2" NPT	GROSS OUTPUT 16,738 MBH
E.(2) SAFETY VALVE 1 1/2" NPT	HEAT RELEASE: (FURNACE ONLY) 146,625 Btu/hr/CuFt
F.(1) BOILER DRAIN 2" NPT	RATED INPUT 20,922 MBH
G.(4) WATER CIRCULATION 2 1/2" NPT	HEATING SURFACE (ASME) 2,506 SqFt
H.(4) HANDHOLE 3" x 4"	FURNACE HEATING SURFACE 170.70 SqFt
J.(1) MANWAY 12" x 16"	FURNACE VOLUME:
K.(1) CLEANOUT 17" ID	FURNACE ONLY 142.69 CuFt
L.(1) AIR VENT/AUXILIARY 2" NPT	
M.(1) LOW FIRE HOLD 1 1/2" NPT	
N.(4) AQUASTAT 1 1/2" NPT	WATER CAPACITY:
P.(1) AQUASTAT 3/4" NPT	(FULL) 3800 Gal @ 31,730 Lbs
Q.(1) STACK TEMP 1 1/2" NPT	
R.(1) SIGHT PORT 1 1/4" NPT	SHIPPING WEIGHT: 36,800 Lbs
S.()	

NOTES

- ALL CONTROLS MOUNTED AS PER SPECIFICATION SHEET.
- SPECIFICATION SHEET TAKES PRIORITY OVER R & D SHEET.
- REAR DOOR SWING:
 - MIN SIDE, MAX REAR
 - MAX SIDE, MIN REAR
- BOILER DESIGN CODE ASME SECTION IV.
- BOILER INSULATED WITH 2" OF INSULATION AND JACKETED WITH 22 GAUGE STEEL.
- ALL DIMENSIONS ARE ± 1/2" UNLESS OTHERWISE NOTED.

SUPERIOR
BOILER

CHECKED BY

DATE

DRAWN BY

DATE

MOHAWK

BOILER MODEL

4-5-2506-W30-

SCALE

DRAWING No

1/62

X

THIS DRAWING IS THE PROPERTY OF SUPERIOR BOILER WORKS & SHALL NOT BE REPRODUCED IN PART OR IN WHOLE, & NONE OF ITS INFORMATION SHALL BE REVEALED WITHOUT PERMISSION OR TO THE DETRIMENT OF THE OWNER. IT MUST BE RETURNED UPON REQUEST.