



BOILER CONNECTIONS

RATINGS & CAPACITIES

LTR DATE

REVISION

BY REPRESENTATIVE:

PROJECT:

NOTES

1. ALL CONTROLS MOUNTED AS PER SPECIFICATION SHEET.
2. SPECIFICATION SHEET TAKES PRIORITY OVER R & D SHEET.
3. REAR DOOR SWING:
 - (1) MIN SIDE, MAX REAR
 - (2) MAX SIDE, MIN REAR
4. BOILER DESIGN CODE ASME SECTION IV.
5. BOILER INSULATED WITH 2" OF INSULATION AND JACKETED WITH 22 GAUGE STEEL.
6. ALL DIMENSIONS $\pm 1/2$ UNLESS OTHERWISE NOTED.

SUPERIOR
BOILER

CHECKED BY

DATE

DRAWN BY

DATE

MOHAWK

BOILER MODEL

4-5-353-W30-

SCALE

DRAWING No

1/32

?

THIS DRAWING IS THE PROPERTY OF SUPERIOR BOILER WORKS & SHALL NOT BE REPRODUCED IN PART OR IN WHOLE, & NONE OF ITS INFORMATION SHALL BE REVEALED WITHOUT PERMISSION OR TO THE DETRIMENT OF THE OWNER. IT MUST BE RETURNED UPON REQUEST.

A.(1) WATER OUTLET	4" NPT	HORSEPOWER	70
B.(1) WATER RETURN	4" NPT	DESIGN PRESSURE	30 P.S.I.G. STEAM
C.(4) LWCO	1" NPT	DESIGN TEMPERATURE	250°F
D.(1) SAFETY VALVE	1 1/2" NPT	GROSS OUTPUT	2343 MBH.
E.(1) SAFETY VALVE	1 1/2" NPT	HEAT RELEASE: (FURNACE ONLY)	147408 BTU/CL.FT.
F.(1) BOILER DRAIN	1 1/2" NPT	RATED INPUT	2929 MBH.
G.(1) WATER CIRCULATION	3" x 4"	HEATING SURFACE (ASME)	355 SQ. FT.
H.(5) HANDHOLE	3" x 4"	FURNACE HEATING SURFACE	40.71 SQ.FT.
J.(1) MANWAY		FURNACE VOLUME:	
K.(1) CLEANOUT	15" ID	FURNACE ONLY	19.87 CU.FT.
L.(1) AIR VENT	1 1/2" NPT		
M.(1) LOW FIRE HOLD	1/2" NPT		
N.(4) AQUASTAT	1/2" NPT		
P.(1) AQUASTAT	3/4" NPT		
Q.(1) STACK TEMP	1/2" NPT		
R.()			
S.()			

WATER CAPACITY:	
(FULL) 720 GAL.	5987 LBS.
SHIPPING WEIGHT:	8500 LBS.