



BOILER CONNECTIONS

A.(1) WATER OUTLET	6" 150# FLANGE
B.(1) WATER RETURN	6" 150# FLANGE
C.(4) L.W.O.D.	1" NPT
D.(1) SAFETY VALVE	2" NPT
E.(1) SAFETY VALVE	2" NPT
F.(1) BOILER DRAIN	2" NPT
G.(1) WATER CIRCULATION	2" NPT
H.(5) HANDHOLE	3" x 4"
J.(1) MANWAY	12" x 16"
K.(1) CLEANOUT	17" ID
L.(1) AUXILIARY/VENT	2" NPT
M.(1) LOW FIRE HOLD	1" NPT
N.(4) AQUASTAT	1/2" NPT
P.(1) AQUASTAT	3/4" NPT
Q.(2) STACK TEMP	1/2" NPT
R.(1) SIGHT PORT	1" NPT
S.(1)	

RATINGS & CAPACITIES

HORSEPOWER	150*
DESIGN PRESSURE	125 PSI WATER
GROSS OUTPUT	8021 MBH*
HEAT RELEASE (FURNACE ONLY)	128,421 BTU/GH*
RATED INPUT	8277 MBH*
HEATING SURFACE (ASME)	787 SqFt
FURNACE HEATING SURFACE	78.88 SqFt
FURNACE VOLUME	48.50 CuFt
TURNOVER VOLUME	23.34 CuFt
WATER CAPACITY:	
(FULL)	1325 GAL • 12,885 LBS
SHIPPING WEIGHT:	13,800 LBS

LOW DATE

REVISION

BY REPRESENTATIVE

NOTES

1. ALL CONTROLS MOUNTED AS PER SPECIFICATION SHEET.
2. SPECIFICATION SHEET TAKES PRIORITY OVER R & D SHEET.
3. BOILER DESIGN CODE ASME SECTION IV.
4. BOILER INSULATED WITH 2" - 8 1/2" DENSITY MINERAL FIBER INSULATION WITH 22 GAUGE STEEL JACKET.
5. ALL DIMENSIONS ARE ±1/2" UNLESS OTHERWISE NOTED.
- *6. HORSEPOWER & RELATED INFO BASED ON 5 SgFt FIRING.

SUPERIOR
BOILER

CREATED BY

DATE

BY

DATE

MOHICAN
7-X-750-W125-

SCALE

1/48

DRAWING No.

?

THIS DRAWING IS THE PROPERTY OF SUPERIOR BOILER WORKS & SHALL NOT BE REPRODUCED IN PART OR IN WHOLE, & NONE OF ITS INFORMATION SHALL BE REVEALED WITHOUT PERMISSION OR TO THE DETRIMENT OF THE OWNER. IT MUST BE RETURNED UPON REQUEST.