

BOILER CONNECTIONS		RATINGS & CAPACITIES	
A(1)	STEAM OUTLET 10" 300# FLANGE	HORSEPOWER	1250
B(2)	LWCO 1" NPT	STEAM PRESSURE	150 PSIG (STEAM)
C(3)	SAFETY VALVE 2" NPT	STEAM OUTPUT	1000 PPH
D(4)	SAFETY VALVE	STEAM (FROM & AT 212°F)	1035 lbs/hr
E(5)	BOILER BLOWDOWN 2" NPT	HEAT ENERGY (FURNACE ONLY)	1,000,000 BTU/HR
F(6)	SURFACE BLOWDOWN 1" NPT	FUEL INPUT	1250 MBTU
G(7)	MANWAY 12" x 16"	HEATING SURFACE (WATER)	1000 SQ.FT.
H(8)	HANDHOLE 2" x 4"	FURNACE HEATING SURFACE	100.53 SQ.FT.
J(9)	CLEANOUT 12" D	FURNACE VOLUME	200.00 CU.FT.
K(10)	FIRESIDE 2" NPT	TURNAROUND VOLUME	127.00 CU.FT.
L(11)	AUXILIARY/VENT 2" NPT	SUPERHEAT VOLUME	300.47 CU.FT.
M(12)	LOW FIRE HOLD 1" NPT	STEAM RELEASE AREA	200.00 CU.FT.
N(13)	STACK TEMP 1/4" NPT	WATER CAPACITY:	
P(14)	SIGHT PORT 1" NPT	(FULL) 10,000 Gal	38,000 Litre
Q(15)		(OIL) 8,500 Gal	32,300 Litre
R(16)		SHIPPING WEIGHT	165,000 Lbs
S(17)			

ITEM	QUAN.	REVISION	BY

NOTES

1. ALL CONTROLS MOUNTED AS PER SPECIFICATION SHEET.
2. SPECIFICATION SHEET TAKES PRIORITY OVER R & D SHEET.
3. BOILER SHOWN ONE ARM SECTION
4. BOILER INSULATED WITH 2" – 4# SAFETY MINERAL FIBER INSULATION WITH 22 GAUGE STEEL JACKET.
5. ALL DIMENSIONS ARE ±1/2" UNLESS OTHERWISE NOTED.
6. HORSEPOWER & RELATED INFO BASED ON 8 lbs/ft FIRING.

BOILER	DRAWN BY	DATE
MOHICAN	CHECKED BY ?	
7-6-7500-S150		
SCALE 1/96	DRAWING No ?	

THIS DRAWING IS THE PROPERTY OF SUPERIOR BOILER WORKS & SHALL NOT BE REPRODUCED IN PART OR IN WHOLE, & COPY OF ITS CONTENTS SHALL BE LOANED WITHOUT PERMISSION OR TO THE DETRIMENT OF THE OWNER, IF SENT TO BE RETURNED UPON REQUEST.