



BOILER CONNECTIONS

A(1) STEAM OUTLET	1/2\"	STEAM INLET
B(1) LINES	1\"	STEAM INLET
C(1) SAFETY VALVE	1/2\"	STEAM INLET
D(1) SAFETY VALVE	1/2\"	STEAM INLET
E(1) SAFETY VALVE	1/2\"	STEAM INLET
F(1) SAFETY VALVE	1/2\"	STEAM INLET
G(1) SAFETY VALVE	1/2\"	STEAM INLET
H(1) SAFETY VALVE	1/2\"	STEAM INLET
I(1) SAFETY VALVE	1/2\"	STEAM INLET
J(1) SAFETY VALVE	1/2\"	STEAM INLET
K(1) SAFETY VALVE	1/2\"	STEAM INLET
L(1) SAFETY VALVE	1/2\"	STEAM INLET
M(1) SAFETY VALVE	1/2\"	STEAM INLET
N(1) SAFETY VALVE	1/2\"	STEAM INLET
O(1) SAFETY VALVE	1/2\"	STEAM INLET
P(1) SAFETY VALVE	1/2\"	STEAM INLET
Q(1) SAFETY VALVE	1/2\"	STEAM INLET
R(1) SAFETY VALVE	1/2\"	STEAM INLET

RATINGS & CAPACITIES

STEAM PRESSURE	150 PSI
STEAM FLOW	100 GPM
STEAM FLOW (AT 200°F)	100 GPM
STEAM FLOW (AT 250°F)	100 GPM
STEAM FLOW (AT 300°F)	100 GPM
STEAM FLOW (AT 350°F)	100 GPM
STEAM FLOW (AT 400°F)	100 GPM
STEAM FLOW (AT 450°F)	100 GPM
STEAM FLOW (AT 500°F)	100 GPM
STEAM FLOW (AT 550°F)	100 GPM
STEAM FLOW (AT 600°F)	100 GPM
STEAM FLOW (AT 650°F)	100 GPM
STEAM FLOW (AT 700°F)	100 GPM
STEAM FLOW (AT 750°F)	100 GPM
STEAM FLOW (AT 800°F)	100 GPM
STEAM FLOW (AT 850°F)	100 GPM
STEAM FLOW (AT 900°F)	100 GPM
STEAM FLOW (AT 950°F)	100 GPM
STEAM FLOW (AT 1000°F)	100 GPM

REV	DATE	REVISION	BY	APPROVED
1				
2				
3				
4				
5				
6				
7				
8				
9				
10				

NOTES	
1. ALL DIMENSIONS SHOWN ARE PER SPECIFICATIONS SHEET.	
2. SPECIFICATIONS MUST BE FOLLOWED EXACTLY OVER R & D SHEET.	
3. DIMENSIONS MUST BE FOLLOWED EXACTLY OVER R & D SHEET.	
4. DIMENSIONS MUST BE FOLLOWED EXACTLY OVER R & D SHEET.	
5. ALL DIMENSIONS ARE 1/4\"	

BOILER	
MODEL NO.	1/72
REVISED BY	?
REVISED BY	?

THIS DRAWING IS THE PROPERTY OF THE COMPANY AND IS NOT TO BE REPRODUCED OR USED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF THE COMPANY. IT MUST BE RETURNED TO THE COMPANY IF NOT BE RETURNED WITHIN 30 DAYS.	
DATE	1/72
REVISED BY	?