


ITEMS TO SHIP LOOSE

STEAM INLET PRV w/NOISE SUPPRESSION
(IF REQUIRED)




- (D) LOW TEMP. RETURN (<180 F)
- (E) MEDIUM TEMP. RETURN (180-227 F)
- (F) HIGH TEMP. RETURN (>227 F)

* STAND HEIGHT SUBJECT TO PUMP NPSH REQUIREMENTS
PUMPS SIZED TO SPECIFIC JOB REQUIREMENTS.
ALL COMPONENTS CONTINGENT UPON FINAL ENGINEERING.
PANEL SIZE MAY VARY DEPENDING ON JOB REQUIREMENTS

DEAERATOR TANK CONNECTIONS

- A. (3) PUMP SUCTION 3 FLG. IN.
- B. (1) WATER INLET 3 FLG. IN.
- C. (1) STEAM INLET 8 FLG. IN.
- D. (1) LOW TEMP. RETURN 3 FLG. IN.
- E. (1) MED TEMP RETURN 2 IN.
- F. (1) HI TEMP RETURN 1 1/2 IN.
- G. (1) DRAIN 2 1/2 IN.
- H. (1) MANUAL VENT 1 1/2 IN.
- J. (1) VENT CONDENSOR 12 FLG. IN.
- K. (1) OVERFLOW 3 FLG. IN.
- L. (1) THERMOMETER 1 IN.
- M. (1) RECIRCULATION 2 1/2 IN.
- N. (1) CHEMICAL FEED 1 1/2 IN.
- P. (1) MANWAY 12 X 16 IN.
- Q. (2) LEVEL CONTROLS 1 IN.
- R. (2) LEVEL ALARMS 1 IN.
- S. (1) RELIEF VALVE 3" 300# FLG. IN.
- T. (1) VACUUM BREAKER 2 1/2 IN.
- U. (1) AUXILIARY CONN 1 IN.

CONNECTIONS NPT UNLESS NOTED, FLANGES 150# UNLESS NOTED



RATING & CAPACITIES

| | |
|--|-----------------|
| DA TYPE | SPRAY |
| CAPACITY | 60,000 LBS./HR |
| DA SECTION CAPACITY | 1,230 GALS. |
| DA STORAGE CAPACITY | 10 MINUTES MIN. |
| DESIGN PRESSURE | 50 PSIG STEAM |
| DESIGN TEMP. | 400° F |
| DEAERATION | .005 CC/LITER |
| OPERATING PRESSURE | 5 PSIG |
| DRY WEIGHT. | 6,061 LBS |
| OPERATING WEIGHT. | 13,050 LBS |
| FLOODED WEIGHT. | 16,624 LBS |
| THE ABOVE WEIGHTS DO NOT INCLUDE PUMPS, TRIM OR CONTROL PANEL. | |
| SHIPPING WEIGHT | |
| TANK (EMPTY) | 4,519 LBS. |
| STAND/PUMPS | 8,460 LBS. |

LTR. DATE

REVISIONS

BY

NOTES

1. ALL CONTROLS MOUNTED AS PER SPECIFICATION SHEET.
2. SPECIFICATION SHEET TAKES PRIORITY OVER DRAWING.
3. ALL DIMENSIONS ARE ±1" UNLESS OTHERWISE NOTED.
4. DA TANK DESIGN CODE ASME SECTION VIII, DIV 1
5. DEAERATE ALL LOADS FROM 3% TO 100% OF RATED OUTLET CAPACITY
6. ELIMINATE TITRATABLE FREE CARBON DIOXIDE TO 0.
7. CORROSION ALLOWANCE 1/16"
8. TANK SEPARATED FROM STAND FOR SHIPMENT.
9. SUPERIOR BOILER, INC. RESERVES THE RIGHT TO FURNISH TRIM SHOWN OR AN EQUAL SUBSTITUTE AS DETERMINED BY SB.

THIS DRAWING IS THE PROPERTY OF SUPERIOR BOILER AND SHALL NOT BE REPRODUCED IN PART OR IN WHOLE, AND NONE OF ITS INFORMATION SHALL BE REVEALED WITHOUT PERMISSION OR TO THE DETRIMENT OF THE OWNER, IT MUST BE RETURNED UPON REQUEST.

| | | | |
|----------------------------------|------|-------------|------|
| SOLD TO: | SB | | |
| JOB: | SB | | |
| DRAWN BY: | DATE | CHECKED BY: | DATE |
| DRAWING NAME DEAERATOR, SPRAY | | | |
| MODEL NO: SS060T155-125 | | | |
| SIZE: 1,230 GALLONS | | | |

SUPERIOR BOILER

SCALE 1/36 DRAWING No