



Features:

- Guaranteed to operate at all loads from 20 to 100% of rated capacity.
- Guaranteed to last under all corresponding temperatures of the saturated steam contained within the vessel.
- Guaranteed against corrosion in excess of 0.001 mils/year.
- Guaranteed to be free of leaks, no steam drains to be.
- All critical rated internal weld connections.
- 10 minute storage capacity minimum.
- Completely packaged option.
- All vessels designed, built and stamped in accordance with the ASME code Section VIII, Div. 1 for Steady.

NOTE

- NOTE:
1. All Shrinkage Aps Approvals And They Or Used For Layout Only.
SHRINKAGE GUM, Inc. Guarantees The Right To Change Shrinkage Due To
Product Revisions Or Job Requirements.
2. For Larger Capacities Consult Factory.

Standard Equipment and Connections:

- [illegible]

Optional Equipment and Connections:

- Pump Shutdown Filter
- Screen Filter: 100 Micron
- Pump Variable Frequency Drive
- Pressure-Temp. Log / Data-Log
- Control
- On/Off or Programmable Preset
- Low Control
- On/Off or Programmable Preset
- Control
- Control Control Panel
- Installation & Logging of Vessel
- Low Water Shut-Off Switch
- Liquid Level Indicator
- Automatic Water Stop
- Control
- 2-Wire System for Water Meter
- Control Valve
- On/Off or Programmable Preset
- Control
- Control Control Panel