



**BOILER CONNECTIONS**

**RATINGS & CAPACITIES**

LTR DATE

REVISION

BY REPRESENTATIVE:

A.(1) STEAM OUTLET	2" NPT	RATED INPUT	1700 MBH
B.(2) LWCO	1" NPT	GROSS OUTPUT	1355 MBH
C.(1) ALWCO	3/4" NPT	DESIGN PRESSURE	150 PSIG
D.(1) SAFETY VALVE	1" NPT	STEAM (FROM & AT 212° F)	1320 Lbs/Hr
E.(1) BOILER BLOWDOWN	1" NPT	HEAT RELEASE: (FURNACE ONLY)	172,697 BTU/CuFt
F.(1) PRESSUREtrol	3/4" NPT		
G.(1) FEEDWATER	1" NPT	HEATING SURFACE (ASME)	132 SqFt
H.(4) INSPECTION	2" NPT	FURNACE HEATING SURFACE	14.97 SqFt
J.(1) SIGHTPORT	2" PIPE	FURNACE VOLUME	9.26 CuFt
K.(1) SURFACE BLOWDOWN	1" NPT	STEAMING VOLUME	4.46 CuFt
L.(2) SIGHT GLASS	1/2" NPT	STEAM RELEASE AREA	3.93 CuFt
M.(1) OVERFLOW	1" NPT		
N.( )		WATER CAPACITY:	
P.( )		(FULL)	116.1 Gals @ 966 Lbs
Q.( )		(NWL)	82.8 Gals @ 689 Lbs
R.( )		SHIPPING WEIGHT:	2,300 Lbs
S.( )			

**NOTES**

1. ALL CONTROLS MOUNTED AS PER SPECIFICATION SHEET.
2. SPECIFICATION SHEET TAKES PRIORITY OVER R & D SHEET.
3. BOILER DESIGN CODE ASME SECTION 1.
4. BOILER INSULATED & COVERED W/22 GA. STEEL JACKET.
5. ALL DIMENSIONS ARE ±1/2" UNLESS OTHERWISE NOTED.



TRIAD

BOILER MODEL  
1600-HP

SCALE 1/24  
DRAWING No ?

CHECKED BY

DRAWN BY

DATE

DATE

DATE

PROJECT:

?

THIS DRAWING IS THE PROPERTY OF SUPERIOR BOILER WORKS & SHALL NOT BE REPRODUCED IN PART OR IN WHOLE, & NONE OF ITS INFORMATION SHALL BE REVEALED WITHOUT PERMISSION OR TO THE DETRIMENT OF THE OWNER. IT MUST BE RETURNED UPON REQUEST.